



DANA LUBRICANTS FACTORY LLC

(A Division of DANA Group)



ISO 9001:2008

ISO 9001:2008 registered company by IIC. (No. : JU – 1306)



Technical Specifications

ATF 1 TYPE A SUFFIX A

Technical Properties	ATF 1 TYPE A-SUFFIX A	
Physical Characteristic	Test Method	Typical Value
Density @15°C ,Kg/L	ASTM D1298	0.876
Kinematic Viscosity @ 40°C , Cst	ASTM D445	40.5
Kinematic Viscosity @ 100°C , Cst	ASTM D445	7.2
Viscosity Index	ASTM D2270	142
Flash Point (COC),°C	ASTM D92	190
Pour Point , °C	ASTM D97	-29



P.O. Box No. 40743, Dubai UAE Tel: 2217273 Fax: 2215940

Email: drdana@danagroups.com , www.danagroups.com



DANA LUBRICANTS FACTORY LLC

(A Division of DANA Group)



ISO 9001:2008

ISO 9001:2008 registered company by IIC. (No. : JU – 1306)



Technical Specifications

ATF DEX II

Technical Properties		ATF DEX II
Physical Characteristic	Test Method	Typical Value
Density @15°C ,Kg/L	ASTM D1298	0.874
Kinematic Viscosity @ 40°C , Cst	ASTM D445	37.8
Kinematic Viscosity @ 100°C , Cst	ASTM D445	7.1
Viscosity Index	ASTM D2270	153
Flash Point (COC),°C	ASTM D92	188
Pour Point , °C	ASTM D97	-31



P.O. Box No. 40743, Dubai UAE Tel: 2217273 Fax: 2215940

Email: drdana@danagroups.com , www.danagroups.com



DANA LUBRICANTS FACTORY LLC

(A Division of DANA Group)



ISO 9001:2008

ISO 9001:2008 registered company by IIC. (No. : JU – 1306)



Technical Specifications

ATF DEX III

Technical Properties		ATF DEX III
Physical Characteristic	Test Method	Typical Value
Density @15°C ,Kg/L	ASTM D1298	0.87
Kinematic Viscosity @ 40°C , Cst	ASTM D445	35.5
Kinematic Viscosity @ 100°C , Cst	ASTM D445	7
Viscosity Index	ASTM D2270	163
Flash Point (COC),°C	ASTM D92	185
Pour Point , °C	ASTM D97	-33



P.O. Box No. 40743, Dubai UAE Tel: 2217273 Fax: 2215940

Email: drdana@danagroups.com , www.danagroups.com