



مصنع دانة لوبريكانتس (ذ م م)
DANA LUBRICANTS FACTORY L.L.C
 (A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

DANA CALCIUM BASE MP-2 GREASE

DANA CBG Water Resistant

Calcium base grease offering excellent water resistance. The selective base oils give an excellent film protection from rust and corrosion to keep the lubrication to the metal surface.

Applications:

DANA CBG Water Resistant Grease

Recommended for used in moderate duty plain and anti-friction bearings wherever non-extreme pressure Grease is recommended.

DANA CBG Water Resistant Grease

Is also used as a process material for variety products.

DANA CBG Water Resistant

Grease can be applied by either centralized pressure grease systems.

TYPICAL CHARACTERISTICS:

NLGI GRADE	1	2	3
COLOR	Light Yellow	Light Yellow	Light Yellow
TEXTURE	Smooth buttery & tacky	Smooth buttery & tacky	Smooth buttery & tacky
DROP POINT, °C	110	115	120
PENETRATION, MM @25°C	310-340	265-295	220-250
SOAP BASE	Calcium	Calcium	Calcium
BASE OIL VISCOSITY @40°C	100cst	100cst	100cst
OPERATING TEMP °C	-30 to 60	-30 to 70	-15 to 80
WATER WASHOUT % OF LOSS @80°C	0.385	0.345	0.312

HANDLING, HEALTH AND SAFETY:

All lubricants and greases, of any kind should be handled with great care.



P.O. Box No. 40743, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: danalubes@danagroups.com, www.danagroups.com