



DANA LUBRICANTS FACTORY LLC
(A Division of DANA Group)



ISO 9001:2008

ISO 9001:2008 registered company by IIC. (No. : JU – 1306)

Page 1/1

COOLANT/ANTI-FREEZE

Meets the following specifications

- ASTM D 3306 GM 6043M Ford ESE-M97B18-C
- ASTM D 4656 GM 1825M Case Corp. MS1710
- ASTM D 4985 Ford ESE-M97B44-A Navistar B1 (B6-008GO)
- ASTM D 5345 Chrysler MS-7170 Cummins 3666132
- SAE J814C Freightliner 48-22880 Detroit Diesel 7SE298
- SAE J1038 Cummins 90T8-4 Ford New Holland 9-86
- SAE J1941 Waukesha 4-19470 John Deere H-5
- SAE J1034 White (GMC Div. Of Volvo) Mack Truck 014GS17004
- GM 1899M John Deere 8650-5 ATA RP 302A

DANA Car Coolant 100% is a concentrate automotive radiator fluid composed of de-mineralized water, ethylene glycol and technologically advanced blend of corrosion inhibitors. It's designed to protect the cooling systems of water-cooled petrol engines.

Applications

DANA Car Coolant is suitable for use in passenger cars' and light diesel vehicles' radiators .Itis a full mono ethylene glycol based coolant with Anti corrosion and anti rust additives for a liquid cooled crankcase. It is harmless to rubber and does not foam or clog radiators. It must be mixed with water to a concentration of 33%, 40% & 50%.

WARNING : NEVER used more than 50%.

TYPICAL PROPERTIES

DANA Car Coolant/Antifreeze	Specific Gravity @ 25 C	Boiling Point C	Freezing Point C	Reserve Alkalinity
Concentration 33 %	1.05	107	-17	
Concentration 40 %	1.055	108	-25	
Concentration 50 %	1.06	110	-36	
Concentration 100%	1.13	165	-50	10 ml min.

