



مصنع دانة لوبريكانتس (ذ م م)  
DANA LUBRICANTS FACTORY L.L.C  
(A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

## DANA GOLD COMPRESSOR OIL

Manufacturer: DANA Lubricants Factory LLC, UAE

**DANA GOLD COMPRESSOR OIL** is a supreme performance air compressor lubricants primarily intended for the lubrication of severe duty rotary screw and vane air compressors. It is formulated with design-specific wax-free synthetic hydrocarbon fluids and a high technology additive system that assures exceptional resistance to oxidation and thermal degradation far superior to mineral oil-based air compressor oils. It provides outstanding equipment protection and reliability for compressors operating under conditions where other air compressor oils are not meeting expectations. DANA GOLD COMPRESSOR OIL provides excellent wear protection and outstanding resistance to oxidation and thermal degradation. Its unique formulation provides the ability to reduce maintenance costs through minimising equipment problems and downstream deposits and carryover. Its high viscosity index ensures effective lubrication at high temperatures.

### EVO

- E- Extra Protection to Clutch & compressor
- V- Value for Money with 70% Extra life
- O- Outstanding Performance in all Weathers

### SPECS

-Meets or exceeds the requirements of Dana EVO compressor oil

Features	Advantages
High Performance Synthetic Base Stocks	Wide temperature range capability
Excellent Water Separability	Improved protection of internal compressor components
Outstanding Oxidation and Thermal Stability	Reduced sludge formation in crankcases and discharge lines
Effective Rust and Corrosion Protection	Reduced blockage of coalescers, inter- and after-coolers
High Load-carrying ability	Reduced wear of bearings and gears



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: [danalubes@danagroups.com](mailto:danalubes@danagroups.com), [www.danalubes.com](http://www.danalubes.com)

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , [www.danagroups.com](http://www.danagroups.com)



مصنع دانة لوبريكانتس (ذ م م)  
DANA LUBRICANTS FACTORY L.L.C  
(A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

Always follow equipment manufacturer's recommendation for the required lubricant performance level and oil drain interval.

**Typical Properties:**

ISO Grade	68
Appearance	B&C
Viscosity @40 °C ASTM D 445, CST	65.8
Viscosity @100 °C ASTM D 445, CST	10.01
Viscosity Index ASTM D 2270	137
RUST CHARACTERISTICS, ASTM D665	PASS
Flash Point, COC ASTM D 92	245
Pour Point, °C ASTM D97	-42
Density @ 15 °C ASTM D 4052	.86

**Handling, Health and Safety**

Lubricant consisting of highly refined mineral oils with specific additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: [danalubes@danagroups.com](mailto:danalubes@danagroups.com), [www.danalubes.com](http://www.danalubes.com)

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , [www.danagroups.com](http://www.danagroups.com)