



مصنع دانة لوبريكانتس (ذ م م)
DANA LUBRICANTS FACTORY L.L.C
(A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

DANA PREMIUM 15W40 GASOLINE ENGINE OIL/ MOTOR OIL / HUILE MOTOR (5000 KM - Engine Warranty)

Performance Standard: API SF

Manufacturer: DANA Lubricants Factory LLC, UAE

DANA GOLD 15w40 GASOLINE ENGINE OIL is a special formulation using mineral base oil technology suitable for passenger car gasoline engine oil exceeding the performance Specification API SF. Developed to provide maximum protection for passenger car. It is available 15w40 API SF viscosity grade to provide fuel saving and to meet long drain requirements. Compatible for all cars running on lead free gasoline.

EVO

- E- Extra Protection to Engine, Clutch & Gears
- V- Value for Money with 70% Extra Mileage
- O- Outstanding Performance in all Weathers

SPECS

-Meets or exceeds the requirements of Dana EVO diesel engine oil

Features	Advantages
Broad Viscosity Range	Superior protection an performance in all weather conditions throughout year
Good Anti Wear Properties	Extends Engine Life
High Thermal Stability &Oxidation Stability	Keeps Engine Clean for smoother operation
Good Corrosion Protection	Protects engine components for long time
Advanced detergency leading to cleaner engines and longer component life.	Excellent Wet clutch performance



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: danalubes@danagroups.com, www.danalubes.com

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , www.danagroups.com



مصنع دانة لوبريكانتس (ذ م م)
DANA LUBRICANTS FACTORY L.L.C
(A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

Performance Levels:

- API SF
- ACEA A2/B3

Always follow equipment manufacturer's recommendation for the required lubricant performance level and oil drain interval.

Typical Properties:

SAE Grade	15w40
Appearance	B&C
Viscosity @40 °C ASTM D 445, CST	110.70
Viscosity @100 °C ASTM D 445, CST	14.40
Viscosity Index ASTM D 2270	132
Flash Point, COC ASTM D 92	220
Pour Point, °C ASTM D97	-24
Density @ 15 °C ASTM D 4052	0.887
TBN (mg KOH/gm) ASTM D 2896	7.0
Sulphated Ash, WT % , ASTM D874	<1.0
CCS , CP, ASTM D5293	6700@ -20 °C
Volatility, % off @ 250 °C ASTM D5800	14max

Handling, Health and Safety

Lubricant consisting of highly refined mineral oils with specific additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.



P.O. Box No. 14761, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: danalubes@danagroups.com, www.danalubes.com

ISO 9001: 2008 CERTIFIED – PART OF DANA GROUP , www.danagroups.com