



مصنع دانة لوبريكانتس (ذ م م)  
**DANA LUBRICANTS FACTORY L.L.C**  
 (A Division of DANA Group)



ISO9001:2008  
 Registered company by IIC (No: JU- 1306)

**DANA LITHIUM BASE MP-2 GREASE**

**Product Description:**

Dana Lithium Base MP-2 grease is premium quality grease and is recommended for variety of greasing application in automotive, agriculture, construction and industrial application. It is recommended for lubrication of wheel bearing, chassis, nipple steering linkages, universal joints etc. This grease provides maximum protection by adhering well to the lubricated bearing surfaces sealing them from dirt and abrasive contaminants.

**Features:**

- Long service life through excellent oxidation stability
- Good rust protection
- Good water wash out properties

**TYPICAL CHARACTERISTICS:**

NLGI GRADE	0	1	2	3
COLOR	Bright Yellow	Bright Yellow	Bright Yellow	Bright Yellow
TEXTURE	liquid	Smooth & Buttery	Smooth & Buttery	Smooth & Buttery
DROP POINT, °C	170	180	194	198
PENETRATION, MM @25°C	355-385	310-340	265-295	220-250
SOAP BASE	Lithium	Lithium	Lithium	Lithium
BASE OIL VISCOSITY @40°C	220cst	220cst	220cst	220cst
OPERATING TEMP °C	-30 to 100	-30 to 100	-30 to 130	-15 to 140
OIL SEPERATION 30HRS, 100c, MASS%	6	5	4	3

**HANDLING, HEALTH AND SAFETY:**

All lubricants and greases, of any kind should be handled with great care.



P.O. Box No. 40743, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: danalubes@danagroups.com, www.danagroups.com