



مصنع دانة لوبريكانتس (ذ م م)
DANA LUBRICANTS FACTORY L.L.C
 (A Division of DANA Group)



ISO9001:2008

Registered company by IIC (No: JU- 1306)

DANA LITHIUM BASE MP-3 GREASE

Product Description:

Dana Lithium Base MP-3 grease is premium quality grease and is recommended for variety of greasing application in automotive, agriculture, construction and industrial application. It is recommended for lubrication of wheel bearing, chassis, nipple steering linkages, universal joints etc. This grease provides maximum protection by adhering well to the lubricated bearing surfaces sealing them from dirt and abrasive contaminants.

Features:

- Long service life through excellent oxidation stability
- Good rust protection
- Good water wash out properties

TYPICAL CHARACTERISTICS:

| NLGI GRADE | 0 | 1 | 2 | 3 |
|---------------------------------------|---------------|------------------|------------------|------------------|
| COLOR | Bright Yellow | Bright Yellow | Bright Yellow | Bright Yellow |
| TEXTURE | liquid | Smooth & Buttery | Smooth & Buttery | Smooth & Buttery |
| DROP POINT, °C | 170 | 180 | 194 | 198 |
| PENETRATION, MM @25°C | 355-385 | 310-340 | 265-295 | 220-250 |
| SOAP BASE | Lithium | Lithium | Lithium | Lithium |
| BASE OIL VISCOSITY @40°C | 220cst | 220cst | 220cst | 220cst |
| OPERATING TEMP °C | -30 to 100 | -30 to 100 | -30 to 130 | -15 to 140 |
| OIL SEPERATION 30HRS, 100°C, MASS% | 6 | 5 | 4 | 3 |

HANDLING, HEALTH AND SAFETY:

All lubricants and greases, of any kind should be handled with great care.



P.O. Box No. 40743, Ajman, UAE Tel: +97142217273 Fax: +97142215940

EMAIL: danalubes@danagroups.com, www.danagroups.com