

DANA LUBRICANTS FACTORY L.L.C

(A Division of DANA Group)



Registered company by IIC (No: JU- 11148)

SAE 5W40 DANA FULLY SYNTHETIC OIL

Performance Standard: API SM/SN

Manufacturer: DANA Lubricants Factory LLC, UAE

Product Description

DANA LUBES EVO 5W40 FULLY SYNTHETIC is an extra high performance petrol engine oil that provides excellent lubrication of today's petrol engines promoting extended engine life. As a result, this product meets or exceeds the specifications of virtually all major European and American engine manufacturers. This extra high performance has been proven in the field in a wide variety of industries, applications, and mixed fleets.

EVO

- E- Extra Protection to Engine, Clutch & Gears
- V- Value for Money with 70% Extra Mileage
- O- Outstanding Performance in all Weathers

Features and Benefits

DANA LUBES EVO 5W40 FULLY SYNTHETIC is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

| Features | Advantages and Benefits |
|--|--|
| High thermal and oxidation stability | Reduced sludge build-up, deposits and viscosity increase |
| TBN reserves | Deposit control and acid neutralization |
| Stay-in-grade shear stability | Wear protection and viscosity control |
| Excellent low temperature properties | Start-up wear protection |
| Meets demanding specifications of key OEMs | One engine oil for mixed fleet operations |

Applications

- High-performance engine oil for all types of cars where this viscosity is recommended



P.O. Box No. 40743, Ajman, UAE Tel: +97142217273 Fax: +97142215940 Email: info@danagroups.com Web: www.danalubes.com

OEM CERTIFICATIONS*
*available



/danalubes



#danalubes



/danagroups

DANA LUBRICANTS FACTORY L.L.C

(A Division of DANA Group)



Registered company by IIC (No: JU- 11148)

- This includes high-performance turbo-charged, supercharged gasoline multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.

DANA LUBES EVO 5W40 meets or exceeds the requirements of the following industry and builder specifications

| | | |
|---------------------------------|----------------------|--------------------|
| API SL/SM/SN | MB-Approval 228.3 | API CF |
| ACEA E7 | Mack EO-M PLUS/EO-N | ACEA A2/B2 |
| Caterpillar ECF-2 | Volvo VDS-3 | Volvo VDS-2 |
| Cummins CES 20078, 20077, 20076 | Renault Trucks RLD-2 | Renault Trucks RLD |
| JASO DH-1 | MTU Oil Category 2 | |

TYPICAL PROPERTIES:

| SL NO | TEST PARAMETERS | TEST METHODS | UNITS | RESULTS** |
|-------|------------------------------|----------------|----------|----------------|
| 1 | Appearance | Visual | NONE | Bright & Clear |
| 2 | Color | ASTM D 1500-12 | NONE | Report |
| 3 | Total Base Number | ASTM D 2896 | mg KOH/g | Min 7 |
| 4 | Density @ 15°C | ASTM D 4052-11 | g/ml | 0.8646 |
| 5 | Kinematic Viscosity @ 40 °C | ASTM D 445 | cSt | 93.09 |
| 6 | Kinematic Viscosity @ 100 °C | ASTM D 445 | cSt | 14.42 |
| 7 | Viscosity Index | ASTM D 2270 | NONE | 161 |
| 8 | Pour Point | ASTM D 97 | °C | -45 |
| 9 | CCS @ -30°C | ASTM D 5293 | cP | 6300 |
| 10 | Flash Point | ASTM D 92 | °C | 214 |

(**The features mentioned above are average values obtained with some variability in production and do not constitute a specification)

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.



P.O. Box No. 40743, Ajman, UAE Tel: +97142217273 Fax: +97142215940 Email: info@danagroups.com Web: www.danalubes.com

OEM CERTIFICATIONS*

*available



/danalubes



#danalubes



/danagroups