مصنع دانة لوبريكانتس (ذمم)

DANA LUBRICANTS FACTORY L.L.C



Registered company by IIC (No: JU- 11148)

Page 1 of 1

DANA LITHIUM BASE GREASE

PRODUCT DESCRIPTION

Dana Lithium Base EP grease is premium quality grease and is recommended for variety of greasing application in automotive, agriculture, construction and industrial application. It is recommended for lubrication of wheel bearing, chassis, nipple steering linkages, universal joints etc. This grease provides maximum protection by adhering well to the lubricated bearing surfaces sealing them from dirt and abrasive contaminants.

FEATURES

- Good rust protection
- Good water wash out properties
- ♣ Long service life through excellent oxidation stability

TYPICAL CHARACTERISTICS

NLGI GRADE	EP 0	EP 1	EP 2	EP 3
COLOR	Light Yellow	Light Yellow	Light Yellow	Light Yellow
TEXTURE	liquid	Smooth & Buttery	Smooth & Buttery	Smooth & Buttery
DROP POINT,°C	175	190	195	198
PENETRATION,MM@25°C	355-385	310-340	265-295	220-250
SOAP BASE	Lithium	Lithium	Lithium	Lithium
4-BALL WELD LOAD ,Kg	250	250	250	250
OPERATING TEMP°C	-30 to 100	-30 to 100	-30 to 130	-15 to 140
OIL SEPERATION 30HRS, 100c ,MASS%	6	5	4	3

^{(**}The features mentioned above are average values obtained with some variability in production and do not constitute a specification)

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.





















