مصنع دانة لوبريكانتس (ذمم)

DANA LUBRICANTS FACTORY L.L.C

(A Division of DANA Group)



Registered company by IIC (No: JU- 11148)

DANA MINERAL ENGINE OIL SAE 50

Performance Standard: CF4/CH4/SF/SL

Manufacturer: DANA Lubricants Factory LLC, UAE

Product Description:

DANA PREMIUM ENGINE OIL is a combination of high performance hydro cracked base fluids and carefully balanced metallic detergents and ash less dispersant additive system, provides excellent overall engine cleanliness in all service conditions. This product meets or exceeds the specification of all major European and American engine manufacturers. This oil is recommended for use in turbo-charged diesel-powered equipment from leading Japanese, European and American Manufacturers, mixed fleets, on-highway light and heavy-duty trucking, off highway industries including construction, mining, quarrying and Agriculture.

TYPICAL PROPERTIES:

Sl No	TEST PARAMETERS	TEST METHODS	UNITS	RESULTS
1	Appearance	Visual	NONE	Bright & Clear
2	Density @ 15°C	ASTM D 4052-11	g/ml	0.8935
3	Color	ASTM D 1500-12	NONE	2
4	Kinematic Viscosity @ 40 °C	ASTM D 445	cSt	204.11
5	Kinematic Viscosity @ 100 °C	ASTM D 445	cSt	20.11
6	Viscosity Index	ASTM D 2270	NONE	114
7	Pour Point	ASTM D 97	°C	-19
8	Flash Point	ASTM D 92	°C	242
9	Total Base Number	ASTM D2896	mg KOH/g	8.52

^{(**}The features mentioned above are average values obtained with some variability in production and do not constitute a specification)

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.



















