مصنع دانة لوبريكانتس (ذمم)

# DANA LUBRICANTS FACTORY L.L.C

(A Division of DANA Group)

Registered company by IIC (No: JU- 11148)

# DANA LUBES EVO SAE 10W30 SEMI SYNTHETIC Performance Standard: API CI-4/CJ-4/CK-4/SL/SN Manufacturer: DANA Lubricants Factory LLC, UAE

### **Product Description**

DANA LUBES EVO 10W30 SEMI SYNTHETIC is an extra high performance Diesel engine oil that provides excellent lubrication of today's Diesel engines promoting extended engine life. As a result, this product meets or exceeds the specifications of virtually all major European and American engine manufacturers. This extra high performance has been proven in the field in a wide variety of industries, applications, and mixed fleets.

#### EVO

- E- Extra Protection to Engine, Clutch & Gears
- V- Value for Money with 70% Extra Mileage
- O- Outstanding Performance in all Weathers

## **Features and Benefits**

DANA LUBES EVO 10W30 SEMI SYNTHETIC is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

Features	Advantages and Benefits	
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase	
TBN reserves	Deposit control and acid neutralization	
Stay-in-grade shear stability	Wear protection and viscosity control	
Excellent low temperature properties	Start-up wear protection	
Meets demanding specifications of key OEMs	One engine oil for mixed fleet operations	

# **Applications**

 Naturally aspirated and Diesel powered equipment from leading Japanese, European, and American manufacturers



مصنع دانة لوبريكانتس (ذمم)

# DANA LUBRICANTS FACTORY L.L.C

(A Division of DANA Group)



- On-highway light and heavy-duty trucking Diesel technology
- Mixed fleets of diesel engines (high speed, four-stroke, turbocharged or naturally aspirated).
- 4 Off-highway industries including: construction, mining, quarrying, and agriculture

# DANA LUBES EVO 10W30 meets or exceeds<br/>the requirements of the following industry and builder specificationsAPI CI-4/CH-4/SL/SJMB-Approval 228.3API CG-4/ CF-4/ CFACEA E7Mack EO-M PLUS/EO-NACEA A2/B2Caterpillar ECF-2Volvo VDS-3Volvo VDS-2Cummins CES 20078, 20077, 20076Renault Trucks RLD-2Renault Trucks RLD

MTU Oil Category 2

### **TYPICAL PROPERTIES:**

JASO DH-1

SL NO	TEST PARAMETERS	TEST METHODS	UNITS	RESULTS**
1	Appearance	Visual	NONE	Bright & Clear
2	Color	ASTM D 1500-12	NONE	Report
3	Total Base Number	ASTM D 2896	mg KOH/g	Min 8
4	Density @ 15°C	ASTM D 4052-11	g/ml	0.872
5	Kinematic Viscosity @ 40 °C	ASTM D 445	cSt	77.5
6	Kinematic Viscosity @ 100 °C	ASTM D 445	cSt	12.0
7	Viscosity Index	ASTM D 2270	NONE	151
8	Pour Point	ASTM D 97	°C	-36
9	CCS @ -25°C	ASTM D 5293	сР	6500
10	Flash Point	ASTM D 92	°C	-36

(\*\*The features mentioned above are average values obtained with some variability in production and do not constitute a specification)

## **Health and Safety**

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.

