

DANA LUBRICANTS FACTORY L.L.C

(A Division of DANA Group)



Registered company by IIC (No: JU- 11148)

DANA LUBES EVO SAE 15W40 SEMI SYNTHETIC **Performance Standard: API CI-4/CJ-4/CK-4/SL/SN** **Manufacturer: DANA Lubricants Factory LLC, UAE**

Product Description

DANA LUBES EVO 15W40 SEMI SYNTHETIC is an extra high performance Diesel engine oil that provides excellent lubrication of today's Diesel engines promoting extended engine life. As a result, this product meets or exceeds the specifications of virtually all major European and American engine manufacturers. This extra high performance has been proven in the field in a wide variety of industries, applications, and mixed fleets.

EVO

- E- Extra Protection to Engine, Clutch & Gears
- V- Value for Money with 70% Extra Mileage
- O- Outstanding Performance in all Weathers

Features and Benefits

DANA LUBES EVO 15W40 SEMI SYNTHETIC is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

Features	Advantages and Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralization
Stay-in-grade shear stability	Wear protection and viscosity control
Excellent low temperature properties	Start-up wear protection
Meets demanding specifications of key OEMs	One engine oil for mixed fleet operations

Applications

- ✚ Naturally aspirated and Diesel powered equipment from leading Japanese, European, and American manufacturers



P.O. Box No. 40743, Ajman, UAE Tel: +97142217273 Fax: +97142215940 Email: info@danagroups.com Web: www.danalubes.com

OEM CERTIFICATIONS*
*available



مصنع دانة لوبريكانتس (ذ م م)

DANA LUBRICANTS FACTORY L.L.C

(A Division of DANA Group)



Registered company by IIC (No: JU- 11148)

- ✚ On-highway light and heavy-duty trucking Diesel technology
- ✚ Mixed fleets of diesel engines (high speed, four-stroke, turbocharged or naturally aspirated).
- ✚ Off-highway industries including: construction, mining, quarrying, and agriculture

DANA LUBES EVO 15W40 meets or exceeds the requirements of the following industry and builder specifications

API CI-4/CH-4/SL/SJ	MB-Approval 228.3	API CG-4/ CF-4/ CF
ACEA E7	Mack EO-M PLUS/EO-N	ACEA A2/B2
Caterpillar ECF-2	Volvo VDS-3	Volvo VDS-2
Cummins CES 20078, 20077, 20076	Renault Trucks RLD-2	Renault Trucks RLD
JASO DH-1	MTU Oil Category 2	

TYPICAL PROPERTIES:

SL NO	TEST PARAMETERS	TEST METHODS	UNITS	RESULTS**
1	Appearance	Visual	NONE	Bright & Clear
2	Color	ASTM D 1500-12	NONE	Report
3	Total Base Number	ASTM D 2896	mg KOH/g	11
4	Density @ 15°C	ASTM D 4052-11	g/ml	0.883
5	Kinematic Viscosity @ 40 °C	ASTM D 445	cSt	118
6	Kinematic Viscosity @ 100 °C	ASTM D 445	cSt	15.5
7	Viscosity Index	ASTM D 2270	NONE	139
8	Pour Point	ASTM D 97	°C	-33
9	CCS @ -25°C	ASTM D 5293	cP	6600
10	Flash Point	ASTM D 92	°C	230

(**The features mentioned above are average values obtained with some variability in production and do not constitute a specification)

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed.



P.O. Box No. 40743, Ajman, UAE Tel: +97142217273 Fax: +97142215940 Email: info@danagroups.com Web: www.danalubes.com

OEM CERTIFICATIONS*
*available

